

AI Face Recognition™

modern technology and digital screens everywhere



PIN Capacity
1500



Card Capacity
1500



Face Capacity
1500



Pro 304mini



Access Control



Battery Backup



Wifi

This powerful, dynamic technology

- FACE • PIN • CARD • RECORD • TCP/IP • ACCESS CONTROL • BATTERY BACKUP • USB DISK

FACE RECOGNITION

Attendance Access Control System

TECHNICAL SPECIFICATION

| S.No | Specification | Parameter |
|------------|--------------------------------|--|
| 1.0 | Display: | |
| 1.1 | Screen Size | 3.5 inch Minimum |
| 1.2 | Type | LCD/LED |
| 1.3 | Resolution | 320 x 240 |
| 2.0 | Video: | |
| 2.1 | Lens | 01 |
| 2.2 | Video Compression Standard | PAL (Default) and NTSC |
| 2.3 | Resolution | 5 MP (video stream: 1080P) |
| 3.0 | Audio: | |
| 3.1 | Audio Output | Built-in buzzer |
| 4.0 | Network: | |
| 4.1 | Wired Network | Support |
| 4.2 | Wi-Fi | Support, 2.4 G, 802.11b/g/n |
| 5.0 | Interface: | |
| 5.1 | Network Interface | 1 RJ-45, 10/100 M self-adaptive |
| 5.2 | Lock Control | 1 |
| 5.3 | Exit Button | 1 |
| 5.4 | TAMPER | 1 |
| 5.5 | USB | 1 |
| 6.0 | Capacity: | |
| 6.1 | Face Capacity Minimum | 1500 |
| 6.2 | Pin Capacity | 1500 |
| 6.3 | Card Capacity | 1500 |
| 6.4 | Event Capacity Minimum | 150000 |
| 7.0 | Authentication: | |
| 7.1 | Face Recognition Distance | 0.3 m ~ 1.5 m |
| 7.2 | Face Recognition Accuracy Rate | > 99% |
| 7.3 | Face Recognition Duration | < 0.2 s |
| 8.0 | General: | |
| 8.1 | Power Supply | 12 VDC Supports power supply by battery in the bracket |
| 8.2 | Power Consumption | ≤ 6 W |
| 8.3 | Working Temperature | -15 °C to 60 °C (14 °F to 131 °F) |
| 8.4 | Working Humidity | 0 to 90% (No condensing) |
| 8.5 | Language | English |